

Personnel Airlocks

ADDITIONAL COVERING



- Completes the range of furniture.
- It allows defining the additional covering to the suspended ceiling and other places where it is required.
- Allows fitting the HVAC grill or the service door.
- When defining the additional covering, e.g. to the suspended ceiling, from 3 sides, each side should be defined separately.
- This is the main reason to indicate position and basic layout for each side.

TECHNICAL DATA

Material design	
intended for	Material
Standard plus*	MDF board
Premium 304	Stainless steel AISI 304, finished SB

Depth "A"
400 mm
450 mm
500 mm
XXX mm
the depth of covering must be selected based on the selection of the depth of the cabinet high. Dimensions 400, 450, 500 are derived from the depth of the cabinet body (without doors)

Width "B"

The requested width to be indicated in millimetres

if the side vertical covering to the partition panel will be included (blinding of the free space between the cabinet and the panel) it is necessary to add the dimension (D) to the basic width of the covering (B). The dimension according to the project is entered, it is necessary to measure / specify only on the basis of the actual state on the construction site.

Height "C"

The requested height to be indicated in millimetres

the height (dimension C) must be measured / specified only on the basis of the actual dimension - the height of the ceiling on the construction site

Side cover to partition panel

Enter the required dimension in millimeters *

without side covering

dimension (E) is always 2000 mm at standard cabinet height

* the dimension is entered according to the project, it is necessary to measure / specify only on the basis of the actual condition on the construction site.

Position of the cover to the partition panel

front and right covering

front and left covering

front covering

dokrytování čelní, levé a pravé

a part of the covering is also a set of mounting angles according to the material design (Standard Plus / Premium 304). The number of mounting brackets is specified by the manufacturer

Installation opening

Additional covering without the installation hole

Atypical - You can define the dimensions of the installation hole

The installation hole is defined by the Q sign and by defining the width x height of the opening in millimetres. E.g. Q350x600

Colour finish

value	intended
White colour. Laminate, basic white, metal RAL 9016	Standard, Standard plus
Colour, stainless steel brushed surface SB	Standard, Standard plus
Stainless steel AISI304	Premium 304
atypical design	Standard, Standard plus
When defining other colour than the selected one, enter Q and subsequently specify the colour of your choice	

MORE INFORMATION, PHOTOS

