

Glazing of partition panels

DOUBLE-SIDED ADDITIONAL GLAZING OF METAL PARTITION



It is inserted into the existing partition panels, thickness 60, 80, 100 and 120 mm.

The window consists of a reinforcing profile, covering frames and sheet glass, thickness 4 or 6 mm.

TECHNICAL DATA

Type

additional double-sided Pharma glazing

Panel thickness

value	surface density
100 mm	37 kg/m ²
120 mm	38 kg/m ²
60 mm	39 kg/m²
80 mm	40 kg/m ²
atypical	kg/m ²
For partitions with a thickness of more than 200 mm, consultation with production is required.	

Structural opening dimensions	
width	height
1000 mm	1200 mm
1000 mm	1500 mm
600 mm	1200 mm
600 mm	1500 mm
800 mm	1200 mm
800 mm	1500 mm
Maximum structural opening dimensions 1500x1800 mm! – Glazing must be fitted across the two panels. This is an atypical design, it is recommended to always consult the production department. Min. height 800 mm, max. dimension 1500 mm.	

Glazing
laminated safety glass, thickness 6 mm
atypical
float glass, thickness 4 mm
Note: As standard the glazing is of clear glass, but it is possible to order an atypical version with milk glass. Float glass design only for glazing with sill 1100mm and above.

Version
with inner frame
atypical

Frame hue and material
metal sheet, hue RAL 9002
metal sheet, hue RAL 9016
Stainless steel AISI 304
Komaxit, hue RAL

Atypical design
Type design
Atypical design
Type design 0 - Unique specification out of offered versions Atypical design Q - atypical design that cannot be uniquely specified by a code

MORE INFORMATION, PHOTOS

