cat. no. 103.03

Glazing of partition panels

SINGLE-SIDED ADDITIONAL GLAZING OF METAL PARTITION



It is inserted into the existing partition panels, thickness 60, 80, 100 and 120 mm.

The window consists of a reinforcing profile, covering frames and sheet glass, thickness 4 or 6 mm.

TECHNICAL DATA

Type
additional single-sided Pharma glazing

Panel thickness	
thickness	**surface density**
100 mm	**23 kg/m2**
120 mm	24 kg/m2
60 mm	**21 kg/m2**
80 mm	**22 kg/m2**

Structural opening dimensions
1200 mm
1500 mm
1200 mm
1500 mm
1200 mm
1500 mm
Min. height 800 mm, max. dimension 1500 mm.

Glazing
laminated safety glass, thickness 6 mm
atypical design
float glass, thickness 4 mm
Note: As standard the glazing is of clear glass, but it is possible to order an atypical version with milk glass. Float glass design only for glazing with sill 1100mm and above.

Frame hue and material
metal sheet, hue RAL 9002
metal sheet, hue RAL 9016
Stainless steel AISI 304
Komaxit, hue RAL

Atypical design
Type design
Atypical design
Type design 0 - Unique specification out of offered versions Atypical design Q - atypical design that cannot be uniquely specified by a code

MORE INFORMATION, PHOTOS